



Clear concrete stain

- Protects against water, stains and graffiti
- High resistance to abrasion
- Respects minerality
- Clear finish, flat or glossy

SPECIFICATION TEXT

Application of a clear water-based impregnating sealer based with acrylic fluoropolymer and siloxane dedicated to the protection of concrete, GRC and UHPC against water and staining like ProtectGuard® WF Special Concrete or similar.
 The product shall have been tested by a laboratory such as LRVision and proven exceptional anti-stain performances.

TESTS

- Water-repellency, stain resistance, graffiti resistance, slipperiness test, capillary absorption, durability (LRVision)

APPLICATION

Implementation according to the manufacturer's recommendations and technical information sheet.

Substrate preparation :

- The conditions of application and preparation of substrates comply with DTU 59.1.
- Removal of efflorescence and cement residue with Guard Remover® Eco Efflorescence & Cement or equivalent.
- Removal of existing paint with Guard Remover® Eco VG Painted Surfaces or equivalent.
- Removal of organic soiling with Guard Wash® or equivalent.
- Removal of greasy stains and residues of form oil with Guard Cleaner® Eco Soiled Floors, Guard Cleaner® Polluted Facades or equivalent.

Application in two layers with an applicator, an HVLP spray gun or an air assisted gun. See technical data sheet.

